

Uniclass EPIC Q411

CI/SfB 5+7 | (72.6) | X

Issue 01.1 | Jan 19

# Technical data sheet - Polaris

# **Description**

A practical, durable chair / bench hybrid for retractable platforms, which combines contemporary looks with an exceptionally durable construction.

A fully automatic version can be specified, where the seats automatically fold and unfold - with no manual operation required.

### **Features**

- Effortless set up backs fold and return into position automatically
- Ergonomically designed seat and backrest
- Blow moulded construction offering strength and a high quality finish
- Folding backrest which flexes to provide excellent lumbar support
- Space efficient design which allows row depths as low as 800mm



Picture shows manual fold-back version with Standard Polaris Backrest









Top: Fully automatic (forward fold) version with Comfoback backrest. Note: Fully automatic operation is only available with the Comfoback backrest shape.

Centre: Manual (fold back) version with Standard Polaris Backrest shape

Bottom: Armrest and cupholder armrest (available with manual fold back option only)



## **Specification**

#### Seat

Blow moulded double skinned high density polyethylene, contoured for comfort and finished in a choice of 15 colours. The lower section and upper section of the seat can be finished in different colours if desired.



Upper and lower sections of the seat

#### **Backrest**

Blow moulded double skinned high density polyethylene in a choice of 15 colours. Note: Fully automatic version features "Comfoback" Backrest and manual version features Standard Polaris Backrest.

#### Chair frame

Cast aluminium, chemically cleaned and finished with an electrostatic applied polyester powder coat.

#### Backrest folding mechanism

There are two options for folding the backrest.

Fully automatic version - The backrests fold forwards as the platforms close. The brackets have internal springs allowing the backrests to rise back into the upright position as platforms open.

Manual folding mechanism (required if armrests or cupholder

Manual folding mechanism (required if armrests or cupholder armrests are specified) - The backrests (and armrests) are manually lowered to the floor before retraction and picked up in groups once the platforms have opened.

#### Armrest

Optional armrest in ABS, mounted to beam, colour black.

#### **Dimensions**

Seat Widths (Centre to Centre): 457mm\*, 483mm\*, 508mm, 533mm, 559mm, 594mm

\*Available for model without arms only

Telescopic Platform Row Depths: 800mm minimum

Telescopic Platform Row Rises:

Comfoback: 300mm minimum

Standard Polaris Back: 260mm minimum

# **Options and accessories**

- Seat numbers and/or aisle letters in black
- Aisle letters
- Armrests
- Cupholder armrests

# Colour Range

